



BRAKE KLEEN

BRAKE & PARTS CLEANER

DEFINITION

BRAKE KLEEN is a non-chlorinated fast drying solvent, formulated to quickly remove asbestos dust, oil, grease, brake fluid, road film and other contaminants from brake linings, pads, mechanical and electric equipment in automotive and industrial sectors.

APPLICATIONS

BRAKE KLEEN is recommended for use in automotive repair shops, bus & trucks terminals, aircraft hangars, printing, industrial, and manufacturing plants.

BRAKE KLEEN cleans & degreases ABS, disc, drum, brake cylinders, brake drums, brake linings, brake shoes, calipers, clutch discs, disc brake pads, discs. It is safe for use on all brake systems including: Springs & Wedge brakes

BRAKE KLEEN is also used in for all electrical appliances, mechanical parts, degreasing before gluing, painting or screen printing.

PRODUCT BENEFITS

- Quickly wash away grease & grime.
- Fast evaporation, non-residual.
- Leaves no residues.
- Will not interfere with subsequent brake operations.
- Brakes regain their efficiency without the need to dismantle.
- Does not corrode metals, rubber, lining & pads.
- Compatible with most plastics and fragile materials.
- Contains no chlorinated hydrocarbons (toxic to humans or to the environment).

TECHNICAL CHARACTERISTICS

Aspect	transparent liquid
Odour	solvent
Colour	colourless
Boiling Point	> 35°C
Flash Point	< -35°C
Auto ignition Temperature	> 200°C
Density (ASTM D4052)	0.6 – 0.7
Water solubility.....	Insoluble
Viscosity.....	7 mm2/s (40°C)

DIRECTIONS FOR USE

Fill in a trigger spraying bottle with **BRAKE KLEEN**. Spray onto the surface and allow to work for a few seconds. If necessary, wipe with a clean cloth. Repeat, if needed, for stubborn dirt or stains. Suitable for use in immersion tank or with a cloth.

STORAGE & SAFETY

Two years, stored in closed original packaging at ambient temperature 5° C and 25°C. Keep in a dry place. Protect from all sources of ignition and heat. The product is flammable and may be irritant in case of prolonged contact. It is advisable to wear gloves, glasses and protection clothes. Work in a well ventilated area and do not smoke.

For further information, please consult the Materials Safety Data Sheet

PACKAGING

Ref. O-0516-J1

Jerry Can 4 x 5L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.