

DECARBOKLEEN 5714

Concentrated Alkaline Decarboniser



DESCRIPTION

DECARBOKLEEN is a powerful alkaline cleaner, formulated for effective degreasing and decarbonising operations of equipment and machines in food industry.

DECARBOKLEEN quickly penetrates to remove burnt oils, fats, greases, and carbonised deposits from surfaces.

APPLICATIONS



DECARBOKLEEN is recommended to dissolve greasy soils and baked on deposits in all food establishments, caterings and food processing industries. Effectively cleans grills, ovens, fryers, pans, hoods, filters and other cooking apparatus.

DECARBOKLEEN may be used in mechanical workshop, whenever stainless steel, cast iron or steel has been subjected to rust, grease or carbon deposits in machining or storage.

PRODUCT BENEFITS

- Highly concentrated formula
- Rapid penetration of carbon grease deposits
- No harsh scrubbing required
- Prevent immediate re-rusting
- Suitable on all stainless steel, cast iron, ferrous and non-ferrous metal.
- Rinse-Free – soils wash right away
- Contains biodegradable surfactants
- Save labour time
- Extremely Economical

PHYSICAL PROPERTIES

Appearance	Viscous liquid
Colour	Pale yellow
Specific Gravity @ 20°C	1.295 ± 0.005
Alkalinity (% NaOH)	26 ± 0.7

APPROVAL / CONFORMANCE



DIRECTIONS FOR USE

AS GRILL AND OVEN CLEANER

As a general guideline mix at 1:10 with water and use through an ORAPI Canyon sprayer.

1. Warm oven or hot plate to 40° C to 60° C.
2. Turn off.
3. Spray solution on oven or on hot plate.
4. Leave surface for 20-30 minutes.
5. Where contamination is heavy, work in with brush.
6. Wipe off with wet rag.
7. Rinse surface clean with potable water.

FOR HEAVY-DUTY CLEANING OF RUST DEPOSITS

Use in hot bath (85°C - 90°C)

Concentration:
0.3%- 0.4% : light Deposits
0.4% - 0.8% : Heavy duty

Material of Construction Compatibility:

DECARBOKLEEN is not suitable for use on aluminum, copper, chrome, brass, galvanized surfaces, tin, zinc, PTFE coated surfaces and other reactive metals.

Do not use on continuous or self-cleaning ovens.

STORAGE & SAFETY

36 months, stored in closed original packaging in a cool and dry environment.

Mildly alkaline and contains detergent materials.

Avoid contact with skin and eyes. Wear suitable protection when handling. In case of contact, immediately flush with running water for at least 15 minutes. Seek medical attention if effects persists.

Avoid breathing mists and vapours. In case of inhalation, remove to fresh air.

If swallowed, rinse mouth thoroughly and give water to drink. DO NOT induce vomiting. Seek medical attention.

Keep away from the reach of children

For further information please refer to the Material Safety Data Sheet.

PACKAGING

Ref: OH-5714-J1Pail 4 X 5L

Ref: OH-5714-O2.....Pail 25L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.