Technical data sheet

8171

FUELMATE Fuel Oil Additive

DESCRIPTION

FUELMATE is designed for removal of excess water from fuel oil with an inbuilt biocide to deal with associated biological fouling.

PRODUCT BENEFITS

- Ensures better atomization and more regular combustion.
- Reduces the frequency of filter cleaning, prevents the clogging or burners
- · Rapidly breaks water emulsions in the oil enabling removal of this contaminant from storage tanks.
- Eliminates biological growth in any water contained in the oil and thus preventing any biological fouling.

PHYSICAL PROPERTIES

Appearance	
Colour	Pale Amber
Odour	.Solvent
Specific Gravity @ 20°C	.0.885 - 0.890
Flash Point (ASTM D56-16a)	.28°C

DIRECTIONS FOR USE

Add **FUELMATE** to the oil in the storage tank in the proportion of 1 L in each 3,000 L of oil. Maintain this concentration in the tank by adding the required amount as often as more oil is added to the tank. Badly sludge tanks should be dosed at triple strength until the sludge has been converted to usable oil. Any water separated will remain in the bottom of the tank. Any water accumulated through the action of the demulsifier FUELMATE will remain free of biological growth until drained or pump away from the tanks.

STORAGE & SAFETY

If swallowed, rinse mouth thoroughly with water. Give plenty of water to drink if conscious. DO NOT induce vomiting because of risk of aspiration. Seek medical advice immediately.

If contact with the eyes; promptly flush affected areas with water for at least 15 minutes. Seek medical attention if effects persist.

If contact with the skin; flush affected areas with copious amount of water immediately. Remove contaminated clothing and launder before reuse. Seek medical attention if effects persist.

For further information please refer to the Safety Data Sheet.

ORAPI APPLIED (S) PTE LTD

No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888 Fax: +65 6268 6474 Inquiries: sin.sales@orapi.com.sg Web Site: www.orapiasia.com

TDS 8171 / 003- 17/04/2019

1/2

The ORAPI Group designs, manufactures and markets, Technical Solutions for Professional Hygiene and Industrial Maintenance. The Group is listed on NYSE Euronext and represented in over 150 countries. ORAPI is certified ISO 9001 and 14001.





PACKAGING

Ref: A-8171-O2 Pail 25L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.

ORAPI APPLIED (S) PTE LTD

No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888 Fax: +65 6268 6474 Inquiries: sin.sales@orapi.com.sg Web Site: www.orapiasia.com

TDS 8171 / 003- 17/04/2019

The ORAPI Group designs, manufactures and markets, Technical Solutions for Professional Hygiene and Industrial Maintenance. The Group is listed on NYSE Euronext and represented in over 150 countries. ORAPI is certified ISO 9001 and 14001.

2/2

