

## TECHNICAL DATA SHEET





## **RENOVEX**

# **Super Concentrated Renovator for Cement, Lime and Concrete Removal**

## **DESCRIPTION**

**RENOVEX** is a super concentrated renovator which removes cement, lime from concrete mixers, transit forms, shovels, metal equipment, machinery, ceramic tile, brick and all masonry work.

## **APPLICATIONS**

**RENOVEX** is used by construction firms, concrete plants, masonry, plastering and ceramic tile contractors. **RENOVEX** removes heavy mortar encrustations from cement trucks, cement mixers, wheelbarrow, metal equipment, shovels, brick, ceramic tile, transit forms etc. **RENOVEX** also removes cement and lime from all equipment.

## PRODUCT BENEFITS

- Deep penetration
- Quickly removes heavy encrustations of mortar and scale
- Safe on most metal equipment and tools found in construction\*
- Removes rust, corrosion and stains from concrete or brick
- Easy to apply by brush or spray applications
- Contains special inhibitors to reduce the attack on bare steel by 98%
- Concentrated for easy and convenient storage
- Very Economical
- Complies with EC directives on biodegradable detergents
- Reduces labour cost and downtime

## TECHNICAL CHARACTERISTICS

Type	Acidic detergent cleaner, renovator.
Appearance	
Colour	Violet
pH	<2
Flammability	Non-flammable
Toxicity	Poison if swallowed. Corrosive to eyes and skin.
Composition	Hydrogen chloride, biodegradable penetrants and special inhibitors.

Orapi Applied (S) Pte Ltd

No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888

Fax: +65 6268 6474





<sup>\*</sup> DO NOT USE ON ALUMINIUM, MAGNESIUM, GALVANIZE OR STAINLESS STEEL.



## TECHNICAL DATA SHEET

## APPROVALS / CONFORMANCES

- Complies with the requirement of the Agri-Food & Veterinary Authority of Singapore.
- Authorized by the U.S. Department of Agriculture (USDA) for use in official establishments operating under the Federal meat, poultry, shell egg grading, and egg products inspection programs.
  Original USDA letter of acceptance is on file in the Home Office.

## **DIRECTIONS**

Chip or scrape off excess accumulations of cement on outer surfaces. Use a scrub pad, stiff brush or coarse steel wool pad dipped in **RENOVEX** solution. Scrub surface thoroughly with the solution. Allow 3-5 minutes penetration and rinse off with clear water. Repeat as necessary for heavy encrustations.

For fresh, relatively light deposits, a solution of one part **RENOVEX** to six parts water is sufficient.

When tools are to be stored, spray on a light coating of **WR+ (805)** for long-lasting rust protection.

DO NOT USE ON ALUMINUM, MAGNESIUM, ZINC (GALVANIZED), OR STAINLESS STEEL.

EQUIPMENT: Mist King Sprayer Poly Sprayer

#### STORAGE & SAFETY

Two years, stored in closed original packaging in a cool and dry environment.

## **WARNING:**

ALWAYS USE FACE MASK (GOGGLES OR FACE SHIELD) AND GLOVES WHEN USING THIS PRODUCT FOR MAXIMUM SAFETY AND PROTECTION. EXERCISE CAUTION TO PROTECT EYES, FACE, AND HANDS. WEAR PROTECTIVE CLOTHING WHEN USING THIS PRODUCT.

For further information please refer to the Safety Data Sheet.

## **PACKAGING**

Ref. O-9085-U2 Drum 205L Ref. O-9085-O2 Pail 25L

## WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM

Orapi Applied (S) Pte Ltd

No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888 Fax: +65 6268 6474

Web Site: www.orapiasia.com

