


MRO Essentials



The Right Product at the right place
Advanced Solutions for Maintenance, Repair and Overhaul

800
REDUCE 4
High Performance Release Agent

Fast acting penetrating agent, developed for mechanical parts exposed to harsh conditions. **Cleans, penetrates, dissolves rust, lubricates and protects.** Provides a water-repellent and phosphate coating. Suitable for badly seized assemblies, bolts, nuts, screws, threads, pulleys. Frees corroded parts without thread damage. Contains no silicone. **Non-flammable. Colour:** Colourless. **Flash Point:** >60°C **Conforms to:** Boeing D6-17487R; Airbus AIMS 09-00-002; US MIL G234 111; NATO Defense XS 66 - AIR DCSEA 604/1


Ref. / Packaging

O 0800 A2	Aerosol 250ML x 12
O 0800 J1	Jerrican 5L x 4
O 0800 O2	Pail 25L

9082
QUIK-SOL
Powerful Industrial Renovator

Concentrated **alkaline surface renovator**, blend of **biodegradable surfactants**, safe solvents and corrosion inhibitors, formulated to **quickly emulsifies grease, oil, grime and industrial soil.** For automotive parts, marine equipment, mining machinery, machine tool, floors, aircraft hangars etc. Suitable for automatic machines. **Non-corrosive. Safe for all surfaces. Non-flammable. Dilution:** up to 1:20.


Ref. / Packaging

O 9082 J1	Jerrican 5L x 4
O 9082 O2	Pail 25L
O 9082 U2	Drum 205L

504
SDI NEW
Powerful Non-Flammable Solvent

Highly effective industrial **degreasing agent**, formulated for effective removal of fuel residues, synthetic oils, **carbonized greases**, tars, gums, varnishes, from mechanical surfaces. **High evaporation leaving no residue behind. Powerful jet spray.** **Non-corrosive. Care to be taken on plastic materials.** For engines blocks, carburetors, Hydraulic Cylinders, boiler burners, elevators, gate rods etc.


Ref. / Packaging

O 504 A5	Aerosol 600ML x 12
O 504 O2	Pail 25L

501
NET'DEX
High Purity Contact Cleaner

Fast evaporating solvent, formulated to **clean and deoxidize switched-off electrical contacts.** Removes oil, grease, dirt, flux and other contaminants. Leaves a light film to **lubricate and protect. Safe on plastic components.** Electronic connectors, circuit breakers, electrical motors, generators, relays, solenoids, switches, plugs and jacks, micro bearings, ignition systems, micro mechanisms etc.


Ref. / Packaging

O 0501 A3	Aerosol 400ML x 12
------------------	--------------------

601
HT 600
Anti-Seize Aluminium Paste

Premium **assembling and mounting paste**, formulated for **equipment operating in harsh oxidizing temperatures and environment.** Provides a **durable protection against rust and oxidation.** Prevents galling, seizing, galvanic action and thread distortion. **Will not harden over time.** Extends life of outdoor and indoor installations. For petrochemical, marine, mine, bolts, nuts, headers flange. **-40°C to +650°C. Colour:** Silver


Ref. / Packaging

O 0601 A3	Aerosol 300ML x 12
O 0601 S1	Pail 5Kg

805
WR+
Moisture Displacer / Penetrating Lubricant

Protects and lubricates mechanical and electrical equipment **exposed to humid and corrosive environments.** Cleans, loosens, lubricates and **leaves a thin film to protect surface from corrosion. Non-flammable. Non-corrosive.** For electrical motors, circuit breakers, generators, ignition systems, injection moulds, tools and machineries. Di-electric breakdown > 40,000 volts. **Colour:** Light Brown **Conforms to:** Airbus PQ 81600; AIR 3634, NATO C 634, US MIL L3150 B Amdt 2.


Ref. / Packaging

O 0805 A4	Aerosol 400ML x 12
O 0805 J1	Jerrican 5L x 4
O 0805 O2	Pail 25L

503
KLEANER
Fast Dry Solvent

Fast acting multi-surfaces solvent cleaner, designed to **quickly dissolves oil, grease and dirt** on mechanical parts. **Leaves no residue.** Powerful jet spray. **Safe on most plastic and fragile materials.** Recommended for engines, locks, piping, circuit boards, relays, surface before painting or bonding. **Non hazardous to humans and safe to the environment.**


Ref. / Packaging

O 0503 A4	Aerosol 400ML x 12
------------------	--------------------

550
ORANGE SOLVENT
Environmentally Friendly Cleaner

Versatile **safe degreasing solvent**, blend of orange oils and synthesised mineral oils which effectively **dissolves grease, heavy oil, bitumen, tar, wax, adhesive, sealant, oil based ink, chewing gum, silicone. Leaves a light film that protects part.** Safe on most surfaces. For all mechanical parts, engines, electric motors, tanks. Can be used in **dip tanks, ultrasonics baths, parts washer.** Non-hazardous, **Non flammable.**


Ref. / Packaging

O 0550 J1	Jerrican 5L x 4
O 0550 O2	Pail 25L
O 0550 U1	Drum 200L

508
A90 H
Non-Flammable Contact Cleaner

Ultra-high purity, **fast drying** electronic grade solvent for **sensitive components.** Penetrates deeply to dissolve grease, oil, dirt, flux, tar and other contaminants. **100% residue-free. Safe to spray on running equipment.** Recommended for circuit boards, switches, connectors, electrical motors, relays, semiconductors, office equipment etc.


Ref. / Packaging

O 0508 A3	Aerosol 330GM x 12
------------------	--------------------

600
TM 900S
Anti-Seize Copper Paste

High performance mounting and assembling paste for **surface treatment and lubrication of parts exposed to harsh temperature and oxidizing environment.** Reduces friction, galling and wear of **mechanisms operating a low speed and high temperatures.** Excellent thermal and electrical conductivity. **Makes disassembling easier even after several years of installation.** For treating tools, shafts, rollers, turbines pins, threaded parts, exhaust systems, nozzles in steelworks, automotive, marine. **-40°C to +1100°C. Colour:** Copper


Ref. / Packaging

O 0600 B6	Tin 500GM x 12
O 0600 S1	Pail 5Kg

627

CT41

EP Weatherproof Grease

Adhesive lithium complex grease, for equipment and mechanisms operating under high shear stresses or high loading conditions. Exceptional extreme pressure lubrication, water and heat resistance. Stays in place and protects mechanism from overload and shock.

Extends lubrication intervals. For construction, industry and marine equipment, sleeve, fifth wheel, trailer wheel bearings, overhead crane, telescopic arm, slide, gear drive etc.

-20°C to +230°C. NLGI: 2.

Timken O.K. Load : 80LB

Colour: Gold Amber



Ref. / Packaging

O 0627 C4 Cartridge 400GM x 12

O 0627 O1 Pail 35LB

623

M23

High Temperature Non-Melt Grease

High temperature bentone grease, designed for superior mechanical stability and moisture resistance. Perfect adhesion to metals, protect mechanisms from overloads and shock loads. Extends lubrication intervals. Recommended for extreme heat applications in automotive, industrial equipment, steel mills, glassworks, petrochemicals, bakeries, brickyards, shafts, articulated joints valves, boilers, extraction fans etc. **-20°C to +260°C.**

NLGI: 2

Colour: Red



Ref. / Packaging

O 0623 C4 Cartridge 400GM x 12

O 0623 O1 Pail 35LB

606

CTDMEP 2

E.P. Synthetic Grease

High Performance lithium complex grease, formulated for mechanisms operating under high temperatures and corrosive atmospheres. Insoluble in water and vapour. Enable mechanisms to operate at high speed from 500 to 8000 RPM. For use in refineries, chemical and petrochemical industries, paper mills and steel mills, bearings, joints, cams, pistons, slides etc.


-30°C to +230°C.

NLGI: 2

DN Factor: 500,000

4-ball EP: 315 Kg

Colour: blue



Ref. / Packaging

O 0606 C4 Cartridge 400GM x 12

O 0606 S1 Pail 5 Kg

806

CB6

Extreme Pressure Chain Lubricant

Synthetic penetrating lubricant for mechanisms operating under severe load at high temperatures. Water-resistant. **Non-staining, does not attract dust.** Excellent adhesion. For chain drives systems, Textile, bottling and food processing equipment subjected to frequent washing, baking ovens, slaughterhouse, bottling equipment etc.

-30°C to +320°C.

Colour: Light yellow

Approved by SEDIS



Ref. / Packaging

O 0806 A3 Aerosol 300ML x 12

O 0806 J1 Jerrican 5L x 4

O 0806 O2 Pail 25L

612

ENG CB 612

Cables & Gears Lubricant

Soft adhesive grease, blend of lithium-calcium complex soaps and extreme pressure additives formulated for cables and open gears. Penetrates effectively to lubricate strands and cores. Excellent resistant to water and moisture.

Reduces noise and energy consumption. Quarries, construction, harbour, cables and drives, cable car, bridge crane, tooth coupling, gear reducer etc.

-50°C to +220°C

NLGI: 0

DN Factor: 50,000

4-ball EP: 780 Kg

Colour: Light brown



Ref. / Packaging

O 0612 A4 Aerosol 400ML x 12

O 0612 S1 Pail 5Kg

605

WSA

EP Waterproof Grease

Premium calcium adhesive grease, for equipment and mechanisms operating under humid or submerged conditions. Insoluble in cold, hot and sea water.

Protects all metal surfaces from humid and corrosive atmospheres. For Marine, offshore, paper industry, petrochemical, winch, trailer balls, valves, sliding gates...

-30°C to +130°C. NLGI: 2.


DN Factor: 50,000. 4-ball

EP: 315 Kg. Colour: green.

Conforms to: MAN 2232/79 -

NATO G460, MIL G 24139

Amdtl. STM 7420B



Ref. / Packaging

O 0605 A3 Aerosol 300ML x 12

O 0605 C4 Cartridge 400GM x 12

O 0605 S1 Pail 5Kg

660

M4

High Temperature MoS2 Grease

High temperature EP bentone grease designed for mechanisms operating under extreme pressure at high temperature. **Does not run off.** Extend lifetime. Recommended for extreme heat applications in automotive, industrial equipment, brickyards, glasswork, bearings, open gears, axles, hinges, exhaust fans, cable tensors etc.

-35°C to 225°C.

NLGI: 2

DN Factor: 150,000

4-ball EP: 240 Kg

Colour: Grey/black



Ref. / Packaging

O 0660 C4 Cartridge 400GM x 12

621

SI4

Silicone Grease

Water-repellent grease formulated for mounting and greasing all mechanisms and electric components operating under water or humid environments. Protects against rusting and electric corrosion. Dielectrical properties and excellent thermal conductivity. Withstands solvent and chemical agents. For relays, connectors, battery terminals, assembly of rubber O-rings, valve, pumps.

-40°C to +200°C. NLGI: 2.

Colour: Translucent

Conforms to: US MIL 8660C;

NATO S 736; NATO G 392;

ATEX 94/9/CE Directive.



Ref. / Packaging

O 0621 T3 Tube 100GM x 12

701

TEFLISS 2

Teflon® Dry Lubricant

Fast drying Hydrophobic lubricant with very low coefficient of friction for mechanisms operating in dusty atmosphere. Protects against oxidation. Water, oil and acid resistant. **Non-staining, Smooth non-sticky finish.**

Use in automotive, wood industry, textile, printing industries for matrices and rollers, sliding doors, sawblades, textile industry, conveyor belts, rotary sliding joints, chain operating under cold conditions, vending machines.

-120°C to +250°C.

Colour: Colourless



Ref. / Packaging

O 0701 A4 Aerosol 400ML x 12

831E

LUB CABLE

Synthetic Cable Lubricant

Fluid adhesive lubricant formulated for cables operating under heavy load. High penetrating action for internal and external cable lubrication.

Contains water repellent and extreme pressure agents. Increases life span of equipment while protecting against corrosion. For crane, cable car, hoist bridge, harbour, petrochemical, construction etc.

Colour: Brown

4-ball wear: 1h at 40 Kg:

<0.4 mm



Ref. / Packaging

O 831E O1 Pail 20L

**507****NDI****Powerful Dry Solvent**

Fast drying industrial solvent designed for **degreasing surfaces before bonding or painting**. Quickly removes oils, greasy deposits, and impurities. **Leaves no residue**. Recommended for locks, chains, cables, parts and piping in contact with gases or **oxygen**. Fast evaporation.

Ref. / Packaging

O 0507 A4	Aerosol	400ML x 12
------------------	---------	------------

**Threadlocking****303****FREINAGE MOYEN****Medium Strength**

Locking and sealing of screws, nuts, threaded parts and assemblies designed **to be disassembled with standard tools**. Protects against corrosion. **Resistance to vibrations**. Withstands oils, water, gas. For automotive and manufacturing. Breakaway Torque on M10: 10 to 20N/mm². **-60°C to +150°C. Colour: blue**.

Ref. / Packaging

O 0303 F3	Bottle	50ML x 6
O 0303 F5	Bottle	250ML x 2

**300****FREINAGE FORT****High Strength**

Permanent locking and sealing of threaded parts and assemblies **which will not be dismantled**. Protects against corrosion. **Resistance to vibrations**. Withstands oils, water, gas. For automotive, aeronautics and manufacturing. Breakaway Torque on M10 > 25N/mm². **-60°C to +150°C. Colour: green. Conforms to: EADS ASNA4030; French Army.**

Ref. / Packaging

O 0300 F3	Bottle	50ML x 6
O 0300 F5	Bottle	250ML x 2

**Retaining****310****FIXPRESS****High Strength Retainer**

High strength resin for **use on press fit components** and bearing where **permanent fixing is required**. Protects against corrosion. Excellent resistance to vibrations. Withstands oils, hot and cold water, gas. For automotive, aeronautics, construction and manufacturing. Shear Strength: 25N/mm². **-60°C to +150°C. Colour: green. Conforms to: EADS ASNA4024; French Army.**

Ref. / Packaging

O 0310 F3	Bottle	50ML x 6
O 0310 F5	Bottle	250ML x 2

**Structural Bonding****125****ORABOND 125****High Performance Adhesive**

Flexible single-component **putty hybrid polymer** formulated for **bonding and sealing all materials**. **High tensile and shear strength**. Provides exceptional bond to **stainless steel, aluminium, wood, glass**. Resists oils, solvents, acids and water. **Can be painted when surface is dry**. Resists UV rays and elements. For sign boards, roof tiles, tiles, automotive, etc. **-40°C to +150°C. Coverage: 1.5m² or 15m. Colour: white.**

Ref. / Packaging


O 0125 C6	Cartridge	290ML x 12
------------------	-----------	------------

**ORAMETAL POCKET****Epoxy Repair Rod**

Steel reinforced epoxy putty, provides fast **permanent repairs to ferrous and aluminum metals**. Excellent resistance to oils, hydrocarbons, hot and cold water, acids and bases. Easy to use and long lasting. **Can be drilled, tapped machined and painted**. Repairs iron pipes, cracked castings, gas and water tanks, radiators, duct work. **-40°C to +150°C. Colour: Grey.**

Ref. / Packaging

O 0221 D1	Stick	125 GM x 12
------------------	-------	-------------

**Protecting Against Corrosion****9964****OXIGO****Rust Remover**

Thixotropic one step **corrosion remover** and **surface renovator** for metallic equipment. Removes rust, degreases, etches and phosphatizes metal surfaces. **Inhibits surfaces against further corrosion**. Suitable for use in marine, automotive, metal equipment, machinery, bridges, tanks, valves, pipes etc. **Colour: Pink.**

Ref. / Packaging

O 9964 J3	Pail	10L
------------------	------	-----

**954****BLOC'RUST****Rust Converter**

Powerful rust passivator which **converts rust to a tough black coating for long term protection**. **Eliminates the need for sandblasting**. Can be painted without preliminary cleaning. High heat resistant after curing. **Over > 100 hrs salt spray testing**. Excellent for outdoor as well as indoor protection. Use in transport, marine, automotive, construction equipment, factories. **Coverage: 10-15 sqm / Ltr. Colour: Brown.**

Ref. / Packaging

O 0954 J1	Jerrican	5Kg x 4
------------------	----------	---------

**706****NZA BRIGHT****Shiny Cold Galvanizing**

Exceptional zinc based coating which provides a **long lasting corrosion protection** of metallic parts exposed to **corrosive atmospheres and extreme weather conditions**. **High zinc content**. Protects **up to 3 years**. Can be painted over. Leaves a **shiny grey metallic finish**. Protects and restores: Railings, welded joints, fences, piping, reservoirs. Salt Spray Test > 400hrs. **-50°C to +200°C. Coverage: 1.5m²/aerosol**

Ref. / Packaging

O 0706 A4	Aerosol	400ML x 12
------------------	---------	------------

**650****NZA MAT****Mat Cold Galvanizing**

Exceptional zinc based coating which provides a **long lasting corrosion protection** of metallic parts **exposed to corrosive atmospheres, salt water and marine environment**. High zinc content. Protects **up to 5 years**. Can be used as a primer for final coat. Leaves a **mat grey finish**. Protects and restores: Highway runners, welded joints, piping, reservoirs. Salt Spray Test > 500hrs. **-50°C to +200°C. Coverage: 1.5m²/aerosol**

Ref. / Packaging

O 0650 A4	Aerosol	400ML x 12
------------------	---------	------------

**804****PROTOR SG 100****Medium Term Corrosion Protection**

Red waxy corrosion inhibitor designed for medium term protection of components exposed to **corrosive atmospheres**. Leaves a **water-repellent** film which is **self-healing**. Dries rapidly. Protect **between 6 months to 1 year indoor**. For use on toolings, injection moulds and machined components during storage. **Conforms to: MIL C81 309 E3; ISO L 6743/8 cat REE. Salt Spray Test > 100hrs. Colour: Red.**

Ref. / Packaging

O 0804 A4	Aerosol	400ML x 12
------------------	---------	------------

**9715****FLEX COTE****Long Term Protection**

Clear methacrylate copolymer formulated for corrosion protection of **bare metal and plastic parts** exposed to prolonged **environment attacks of elements**. Leaves a **tough coating which is waterproof and scratch-resistant**. Dries rapidly. Restores surfaces to smooth finish. Use in automotive, construction, marine, shipping, refineries & oil fields, industrial plant, stainless steel surfaces and pipes. **Coverage: 10m² / L. Colour: Colourless.**

Ref. / Packaging

O 9715 O2	Pail	25L
------------------	------	-----



799

REDUCE AL

De-Seizing Agent

High performance penetrating **de-seizing agent** which **cleans, lubricates and protects surfaces** from corrosion. Preventive and curative action against rust. Low surface tension. **Water resistant. Odourless.** Recommend for used on frozen nuts, bolts, fittings, hinges, shackles, lock mechanisms, springs, valves, in **food processing, pharmaceutical and healthcare industry.**
Colour: Colourless



Ref. / Packaging

O 0799 A2 Aerosol 250ML x 12

544

ORASOLV T

Odourless Solvent Cleaner

Multi-purpose **high evaporation solvent** for effective cleaning of **mechanical parts** in food and pharmaceutical plants. **Excellent compatibility on seals, rubbers, gaskets and all plastics.** Degreases mechanical parts, stainless steel equipment, **electric devices,** windings, collectors. Can be used for cleaning surfaces before bonding or painting.
Flash point: 41°C
Dielectric strength: 60kV/cm
Colour: Colourless



Ref. / Packaging

O 0544 J1 Jerrican 5L x 4
O 0544 O2 Pail 25L

812

SILAL

Silicone Lubricant

Premium **semi-greasy** agent formulated for the lubrication of mechanisms in food service **operating in high moisture and dusty conditions.** **Water repellent, non-staining.** Chains, conveyors, open mechanisms, food racks, chutes, assembly lines, slides, plastic gears, release of injected and moulded plastic parts.
Non-toxic, odourless.
40°C to +180°C
Colour: Colourless



Ref. / Packaging

O 0812 A4 Aerosol 400ML x 12

707

ORAFLON AL

TEFLON® Based Lubricant

High technology lubricant, blend of synthetic oil, micronized Teflon® particles and extreme pressure additives developed to reduce lubrication frequency of **equipment exposed to temperatures, load and humidity.** Protects surfaces from corrosion. **Water-resistant.** Does not stain. For pins, runners, bottle conveyors, overhead conveyors, trolley wheel pins, abattoirs, poultrys etc.
-30°C to +230°C
Colour: White



Ref. / Packaging

O 0707 A4 Aerosol 400ML x 12

615

CT 615

Extreme Pressure Grease

Premium white grease, blend of **codex oil and calcium complex** thickener food service equipment **operating under high loads and temperatures.** **Insoluble in water, vapour, blood, alkaline and acids solutions.** Non-staining. For ball bearings, articulated joints, shafts, cams, pistons, valves, packing machines and wrapping equipment.
-20°C to +160°C (200°C in peak)
NLGI: 2, DN Factor: 350,000
4-ball EP: 315 Kg
Colour: White Opaque



Ref. / Packaging

O 0615 C4 Cartridge 400GM x 12
O 0615 O2 Pail 25Kg

609

CT 609

Multi-Purpose Bearing Grease

High quality **translucent** grease, blend of **codex oil and inorganic thickener** for mechanism operating in agriculture, food and pharmaceutical industries. **Does not stain, excellent water resistance.** Use on bearings, rods, packaging, linkages, packaging industry and breweries.
-30°C to +150°C.
NLGI: 2. Drop point: None
DN Factor: 350,000
4-ball EP: 180 Kg
Colour: Translucent



Ref. / Packaging

O 0609 A4 Aerosol 400ML x 12

620

SITEF GRADE 2

TEFLON® Based Silicone Grease

High performance grease for lubrication of **equipment subjected to acid or alkaline conditions.** For mechanisms **operating at low speed under extreme high or low temperatures:** linear bearings, ball bearings, tap fittings, valves, pneumatic mechanisms and jacks, abattoirs, bakeries. **Excellent resistant to water washout.** Does not stain. **-60°C to +280°C.**
NLGI: 2. Drop point: None
4-ball EP: 150 Kg.
Colour: White



Ref. / Packaging

O 0620 B7 Tin 1Kg x 6

580

ORANGE CREAM

Citrus Hand Cleaner

Neutral hand washing lotion, blend of **natural citrus oil, biodegradable surfactant and polymeric beads** which combines effective cleaning with gentle rubbing action. Removes the toughest grease, oils, grime, soot, coal, gasket cement, glues and inks. Contains glycerine to **hydrate and care for chapped hands.** Leaves a pleasant citrus perfume. **Contains no petroleum solvents.** Mines, oil rigs, manufacturing and engineering workshops, garages etc. **Colour:** Orange



Ref. / Packaging

O 0580 J0 Jerrican 3.8L x 4

9957

DERMA TUFF

Heavy Duty Hand Cleaner

Premium **Mildly abrasive protein-bolstered** hand cleaner, especially formulated to dissolve hard-to-remove grease and grime with or without water. Effective to **remove grease, oil, dirt, paint, tar, shellac, duplicator ink, carbon black, adhesive and dye.** **Contains no harsh solvent. Leaves hands smooth with a pleasant scent.** Suitable for use in mines, oil rigs, manufacturing and engineering workshops, garages etc.
Colour: Orange



Ref. / Packaging

O 9957 J0 Jerrican 4L x 4

575

ULTRA CLEAN WIPES

Hands and Surfaces Cleaner

Wipes impregnated with a **natural plant extract solution,** designed for **effective degreasing of hands, tools and equipment** heavily soiled by oils, greases, inks paints, petrol, tar, adhesive residue and soot. Cleans hands without water directly on site.
Hypo-allergenic. Leaves a pleasant mandarin scent on hands.
Colour: Pink wipes



Ref. / Packaging

O 0575 S9 Bucket 70 wipes

Since 1968, **ORAPI** (Office of Research and Application of Products for Industry) has been understanding and anticipating the requirements of the manufacturing industry. Providing mechanical and maintenance engineers, technologically Advanced Solutions, to improve the reliability and durability of their tools, while bringing down their operating costs.

With 8 factories and a distribution coverage in 150 countries, **ORAPI Designs, Manufactures and Distributes a wide range of products for Maintenance and Process in most industrial sectors.** **ORAPI** has become the specialist in the state of the art products within the field of cleaning, lubricating, protecting, bonding, sealing and machining.

ORAPI products help to **maintain, repair, rebuild, renovate and restore damaged and worn parts to quickly return equipment to full operations.**

The high quality and manufacturing standards of **ORAPI** products are continually endorsed by our customers and tested by independent certification bodies, such as: **ISO standards (9001 & 14001)**, food standards (NSF, InS and FOOD CANADA), military standards (NATO, US MIL), aeronautical standards (ASNA, Aims, Boeing), international standards (BS: British, DIN: German, AFNOR: French), etc. These audits and certifications often award **ORAPI** the top grades, while respecting the standards of high quality in terms of products innovation and advance technology.

The **ORAPI** laboratories of Research and Development are actively preparing for the future. **ORAPI** is committed to ensure safety and developing high quality products that are environmental friendly. Our goal is to provide technological innovations which are safe to the public health and maintaining the quality of the environment.



ASIA & MIDDLE EAST

- **SINGAPORE**
ORAPI APPLIED (S) PTE LTD
No. 26 Tuas Avenue 13
Singapore 638992
Tel: +65 6265 2888
Fax: +65 6268 6474
E-mail: sin.sales@orapiasia.com
- **MALAYSIA**
ORAPI APPLIED (M) SDN BHD
No. 10, Jalan PJU 3/49 – PJU 3,
Sunway Damansara
47810 Petaling Jaya – Selangor,
Malaysia
Tel: +60-3-7805 3805
Fax: +60-3-7880 5805
E-mail: msia.sales@orapiasia.com
- **THAILAND**
ORAPI APPLIED (T) CO.,LTD
No 55/75 Klonglamjiaik Road.,
Nuanchan, Buengkum,
Bangkok 10230 – Thailand
Tel: +66 2508 1342
Fax: +66 2508 1343
Email: thai.sales1@orapiasia.com
- **UAE**
ORAPI MIDDLE EAST L.L.C.
729 Business Village Main
Building Block B
PO Box 120509, Dubai
United Arab Emirates
Tél: +971 (0) 42942947
Fax: +971 (0) 42942948
Email: uae.sales@orapi.ae

PACIFIC

- **AUSTRALIA**
ORAPI PACIFIC PTY LTD
Tel: +613 9701 5373
E-mail: info@viclube.com.au
- **MAURITIUS**
ORAPI PACIFIC CIE LTD
Tel: +230 208 1477
E-mail: admin.prolub@intnet.mu
- **NEW CALEDONIA**
ORAPI PACIFIC SFAC SARL
Tel: +687 25 15 40
E-mail: sfac@sfac.nc
- **SOUTH AFRICA**
ORAPI AFRICA LTD
Tel: +27 11 453 17 13
E-mail: info@orapiafrica.co.za

AMERICAS

- **CANADA**
ORAPI CANADA LTD
Tel: +1 514 735 32 72
E-mail: jeanf@orapi-canada.com
- **MARTINIQUE**
ORAPI MHE
Tel: + 596 77 37 07
E-mail: info@mhe-martinique.com

EUROPE

- **FRANCE**
Worldwide Headquarter
ORAPI FRANCE
Parc Industriel de la Plaine
de l'Ain
225, allée des Cèdres
01150 Saint-Vulbas
Tel: +33 (0)4 74 40 20 20
Fax: +33 (0)4 74 40 20 21
Web: www.orapi.com
E-mail: contact@orapi.com
- **BELGIUM**
ORAPI APPLIED BELGIUM S.A
Tel: +32 2 2800 736
E-mail: sales@orapiapplied.be
- **NORWAY**
ORAPI APPLIED NORWAY
Tel: +47 333 66 000
E-mail: kundeservice@orapi.no
- **UNITED KINGDOM**
ORAPI APPLIED LTD
Tel: +44 121 525 4000
E-mail: info@orapiapplied.com
- **FINLAND**
ORAPI NORDIC OY AB
Tel: +358 9 894 6430
E-mail: sales@orapinordic.net
- **NETHERLAND**
ORAPI APPLIED NEDERLAND B.V
Tel: +31 172 43 72 21
E-mail: sales@orapiapplied.com
- **POLAND**
ORAPI TRANSNET SP. z o.o.
Tel: +48 61 813 86 40
E-mail: mariusz.polkowski@orapi.com
- **SWEDEN**
ORAPI NORDIC OY AB
Tel: +46 18 506 010
E-mail: info@orapi.se
- **ITALY**
ORAPI ITALIA SRL
Tel: +39 06 916 10576
E-mail: info@orapi.it
- **SPAIN**
ORAPI TRANSNET ESPAÑA, SL
Tel: +34 974 480 828
E-mail: adminote@orapi.com

www.orapiasia.com

Follow us on:



ORAPI[®]
GROUP