

PROFESSIONAL DISHWASHING MACHINES

Select from Undercounter / Hood type / Conveyor type machines ♦ Site surveys / Recommendations / Installations ♦ SOP / Dispensers provided ♦ On site training ♦ 24/7 Technical support ♦ Regular service maintenance.



MODEL					
	Upster U400	Upster U500	Upster H500	Ecostar K200M	Ecostar K260M
TYPES	UNDERCOUNTER (Glassware)	UNDERCOUNTER (Dishware & Glassware)	HOOD	SINGLE TANK	DOUBLE TANK
DIMENSIONS	H 700–730 mm, W 460 mm, D 600 mm	H 820–850 mm, W 600 mm, D 600 mm	H 2050/2288* mm, W 635 mm, D 750 mm	H 1400mm, W 1550mm, D 830mm	H 2010mm, W 2050mm, D 830mm
ENTRY HEIGHT	H 300 mm	H 320 mm	H 440 mm	H 450MM	H 450MM
BASKETS DIMENSIONS	400 x 400 mm	500 x 500 mm	500 x 500 mm	500 x 500 mm	500 x 500 mm
WASH CAPACITY	up to 30 baskets/h	up to 30 baskets/h	up to 60 baskets/h	130-200 baskets/h	165-250 baskets/h
CYCLE DURATION	120/180 sec	120/180 sec	60/90/210 sec	60-180sec	180-240 sec
WASH CYCLE					
WASH TEMPERATURE	50-55 deg c	50-55 deg c	50-55 deg c	50-55 deg c	50-55 deg c
RINSE TEMPERATURE	up to 85 deg c	up to 85 deg c	up to 85 deg c	up to 85 deg c	up to 85 deg c
WATER					
WATER CONSUMPTION (Final Rinse)	2.2 l/baskets	3 l/baskets	3 l/baskets	360 l/h	400 l/h
TANK VOLUME	11 liters	20 liters	22 liters	90 liters	140 liters
WATER SUPPLY TEMPERATURE	Ambient	Ambient	Ambient	Ambient	Ambient
WATER SUPPLY PRESSURE	Min 2.5 bar	Min 2.5 bar	Min 2.5 bar	Min 2.5 bar	Min 2.5 bar
ELECTRICAL					
POWER SUPPLY (V/Hz/PH)	220V/50Hz/1	220V/50Hz/1 or 400V/50Hz/3	400V/50Hz/3	400V/50Hz/3	400V/50Hz/3
TOTAL LOAD (KW) Amperage	3.6 kW	5.1 kW	11.8 kW	33.03 kW	48.1 kW
WASH PUMP POWER (KW)	0.55	0.55	0.75	1.7	1 x 0.55/1 x 1.7
FEATURES					
DOOR OPENING	Front	Hood	Hood	Vertical sliding	Vertical sliding
CONTROL PANEL	Mike 1	Mike 1	Mike 1	K-tronics	K-tronics
SELF DIAGNOSTIC SYSTEM	YES	YES	YES	YES	YES
THERMOSTOP FUNCTION	YES	YES	YES	YES	YES
ANTI-CLOGGING WASH ARM	YES	YES	YES	YES	YES
TANK CONSTRUCTION	Single piece	Single piece	Single piece	Single piece	Single piece
IN-LINE 600mm DRYER	Optional	Optional	Optional	Optional	Optional
REVERSIBLE FLOW DIRECTION	Optional	Optional	Optional	Optional	Optional
BUILT-IN DETERGENT DISPENSER	Optional	Optional	Optional	Optional	Optional
BUILT-IN RINSE AIR DISPENSER	Optional	Optional	Optional	Optional	Optional
DRAIN PUMP	Optional	Optional	Optional	Optional	Optional