

Technical data sheet

APPSORB Liquid Absorber

3663



DESCRIPTION

APPSORB is an extremely effective absorbent that is used in a wide range of industries, tanneries, canning plants, packing plants, textile mills, garages, workshops, petrol stations, etc.

APPSORB can be used on many types of lubricants, light oils, cutting oils, soluble oil emulsions, water, grease, acids, solvents, syrups and other liquid and semi-liquid materials.

APPLICATION

APPSORB is especially used for:

- Reclamation and preservation of floors.
- Absorptive banking around machinery and walls.
- Reclamation of soil-soaked gloves, clothing, belting, etc.
- Annealing of high carbon steel, cooling of forgings.
- Elimination of bleeding of pitch, tar, creosote, etc., from treated wood.
- Absorption of spilled cyanide in case hardening processes, or optical rouge in polishing rooms.
- Use as a sweeping compound after saturation with oil.
- Protection of rubber hoses, tyres, from oil rot.
- Absorption of oil and grease drippings.

PRODUCT BENEFITS

- Versatile, granulated absorbent.
- Easy and convenient to use.
- Reduces maintenance of floors.
- Improves working conditions.
- Lowers risk of accident.
- Will not support combustion.
- Absorbs more than its own weight of oil, water or other liquids.
- Will not break down or "mud" even after prolonged use.

PHYSICAL PROPERTIES

Appearance	Fine granules
Colour	
Flammability	



TDS 3663 / 002- 08/02/2022

he ORAPI Group designs, manufactures and markets, Technicc olutions for Professional Hygiene and Industrial Maintenance. Th roup is listed on NYSE Euronext and represented in over 100 countries RAPI is certified ISO 9001 and 14001.



DIRECTIONS FOR USE

Using **APPSORB** is simplicity itself. Just sprinkle **APPSORB** on the contamination, allow to stand for a short time and sweep up.

STORAGE & SAFETY

NON-HAZARDOUS

Avoid contact with eyes and skin. Wear safety glasses if dusting is likely to occur. Wear rubber gloves if prolonged skin contact is expected. Avoid breathing dust. Refer to label or MSDS for further safety information

For further information please refer to the Material Safety Data Sheet

PACKAGING

Ref: A-3663-H3 Pail 17 Kg

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.



2/2

Technical data sheet

ORAPI APPLIED (S) PTE LTD

No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888 Fax: +65 6268 6474 Inquiries: sin.sales@orapi.com.sg Web Site: www.orapi.com

TDS 3663 / 002- 08/02/2022

The ORAPI Group designs, manufactures and markets, Technica Solutions for Professional Hygiene and Industrial Maintenance. The Group is listed on NYSE Euronext and represented in over 100 countries ORAPI is certified ISO 9001 and 14001.