

AVIOKLEEN II

Concentrated Exterior Aircraft Cleaner

4935



DESCRIPTION

AVIOKLEEN II is heavy-duty, high quality viscous aqueous detergent formulated for the removal of soils from exterior surfaces of aircrafts.

AVIOKLEEN II liquefies and removes greases, oils, stains and marks from surfaces leaving a residue free finish.

APPLICATIONS



AVIOKLEEN II is a versatile formula designed for all exterior wash applications by brush, mop, non-atomising spray and is suitable for use as a wipe on - wipe off.

AVIOKLEEN II is particularly effective for cleaning landing gears, control flaps, wheel wells etc.

PRODUCT BENEFITS

- Powerful detergency action.
- Enhanced viscosity to increase contact time with the soils.
- Suitable for dry wash and wet wash.
- Safe on all exterior surfaces, paints and acrylic plastics.
- Good hard water tolerance.
- Dries residue free.
- Non-flammable.
- Concentrated formula to minimize shipping cost.
- Very Economical.
- Enhance corporate image.
- Reduces labour cost and downtime

PHYSICAL PROPERTIES

Appearance	Viscous liquid
Colour	Yellow
Odour	Mild detergent
Density	1.05 ± 0.01
pH (neat)	12.1 ± 0.3
Flash Point.....	Non-flammable

APPROVALS / CONFORMANCES

- AMS 1526B
- Boeing D6-17487 Revision L
- Fokker

DIRECTION FOR USE

Prepare the desired cleaning solution and apply by brush, mop or non atomising spray to the surface to be cleaned. Allow solution to penetrate the soil, then agitate with brush or similar. Rinse thoroughly with fresh water.

AVIOKLEEN II can also be used in a wipe on - wipe off application. Apply to the surface using a hand spray or similar. Using wet rags or pads, wipe the soiled surface. Using clean rags, wipe the surface dry, removing the soil and solution.

Dilutions:

Light to Medium Soil: 1 part **4935** with 10 - 20 parts of water.
Medium to Heavy Soil: 1 part **4935** with up to 1 - 10 part of water.

STORAGE & SAFETY

Three years, stored in closed original packaging in a cool and dry place. **NON HAZARDOUS**. Avoid contact with eyes and skin. Wear safety glasses if splashing is likely to occur. Wear rubber gloves if prolonged skin contact is expected.

For further information please refer to Safety Data Sheet.

PACKAGING

Ref: A-4935-O2 Pail 25L
Ref: A-4935-U2 Drum 205L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.