

AVIOKLEEN HD

Heavy Duty Aircraft Cleaner

4553



DESCRIPTION

AVIOKLEEN HD is a thixotropic heavy-duty water based cleaner formulated for the removal of oily soils, greases and carbons from painted and unpainted exterior metal surfaces of aircrafts.

APPLICATION



AVIOKLEEN HD effectively removes jet soils, such as synthetic oil films, heavy greases, carbons and exhaust residues from metal surface, underbelly, landing gear, wheel well, flap, etc.

PRODUCT BENEFITS

- Excellent oil and grease penetration.
- Clings to vertical and overhead surfaces.
- Enhanced viscosity to increase contact time with the soils.
- Safe on all metals, epoxy and polyurethane paints.
- Suitable for use on all models of jet aircrafts.
- Colour identified.
- Free rinsing.
- Non-flammable.
- Concentrated formula to minimize shipping cost.
- Very Economical.
- Enhance corporate image.
- Reduces labour cost and downtime.

PHYSICAL PROPERTIES

Appearance	Viscous liquid
Colour	Green
Odour	Solvent
Specific Gravity @ 20°C	0.963 ± 0.01
pH (neat)	9.9 ± 0.1
Flash Point	Non-flammable

APPROVALS / CONFORMANCES

- AMS 1533A

DIRECTION FOR USE

Apply neat to contaminated area with non-atomizing spray (Graco, Larius) or brush. Allow to contact surface for at least 15 minutes. Agitate the surface with suitable brushes. Re-apply **AVIOKLEEN HD** if soil is not completely penetrated. Rinse with pressure stream of fresh water.

Materials of construction Compatibility:

AVIOKLEEN HD is safe on all metals used for aircraft construction, particularly high strength steel. Safe for use on polyurethane and epoxy paints. Plastic materials should be tested before contact.

STORAGE & SAFETY

Two years, stored in closed original packaging in a cool and dry place. Goggles, gloves and safety clothing should be worn when applying **AVIOKLEEN HD**. If accidental contact with the skin occurs, flush with copious quantities of water. If contact with the face or eyes occurs, remove contact lenses, then flush with copious quantities of water. Seek medical advice.

For further information please refer to the Material Safety Data Sheet.

PACKAGING

Ref: A-4553-O2Pail 25L
Ref: A-4553-U2.....Drum 205L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.