

AVIOSOLV II

V || 8300





DESCRIPTION

AVIOSOLV II is sophisticated blend of hydrocarbon solvents and cleaning agents formulated for effective cleaning and degreasing of aircraft metal components.

AVIOSOLV II is a fast drying product that does not leave a residue after application.

APPLICATION







AVIOSOLV II is particularly recommended for the removal of brake dust, oil, grease and general soil from brake components and engine parts.

AVIOSOLV II may also be used as a multi-purpose degreasing fluid and solvent wipe on wheel bay area, control flaps and any other mechanical parts.

PRODUCT BENEFITS

- Powerful degreasing action.
- Leaves a residue free finish for improved cleaning.
- Safe on all metals.
- Exhibits quick drying evaporation to speed up the cleaning process.
- Low toxic and low odour for greater user safety and comfort.
- Multi purpose product to reduce inventory and cost.
- Contains no Chlorinated Hydrocarbons for a more environmentally friendly approach.

PHYSICAL PROPERTIES

Appearance	Liquid
Colour	Colourless
Odour	Low solvent odour
Specific Gravity @ 15°C	0.749
Flash Point (TCC)	>24°C
Solubility	



Web Site: <u>www.orapiasia.com</u>

TDS 8300 / 004 – 14/02/2022





APPROVALS / CONFORMANCES

- Boeing D6-17487 Rev. L,
- Douglas CSD # 1 issue 1988
- Fokker,
- Honevwell
- Rolls Royce 1/257B

DIRECTION FOR USE

Use as supplied by brush, wipe or immersion. Spray sufficient amount to cover the surface and allow several seconds for the soil and grease to liquefy. Follow with a second application to remove all dissolved and suspended soil. Wipe or air dry.

NOTE: Compatibility test is required before use on plastics, paints and rubbers.

STORAGE & SAFETY

Two years, stored in closed original packaging in a cool and dry place. HAZARDOUS. Flammable Liquid, Avoid sources of ignition. Avoid breathing vapours. Use in well ventilated area. Wear safety glasses & suitable gloves when handling.

For further information please refer to the Material Safety Data Sheet.

PACKAGING

Ref: A-8300-O2	Pail 25L
Ref: A-8300-U2	Drum 205L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRÉSS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.

Group is listed on NYSE Euronext and represented in over 150

countries. ORAPI is certified ISO 9001 and 14001.

