

MAGNUSPRAY 205

Multi-Metal Spray Wash Liquid

DESCRIPTION

MAGNUSPRAY 205 is a non-caustic liquid wash spray cleaner, it is a blend of alkaline builders, water conditioners, and biodegradable low foaming surfactant and corrosion inhibitors. It uses include spray wash cleaning of ferrous and non-ferrous metals. Suitable for use at room temperature in many applications

PRODUCT BENEFITS

- Highly alkaline for cleaning wide variety of soils
- Versatile-multi-metal safe
- Suitable for use in moderately hard water
- Can provide in-process rust protection
- Low foaming above 25°C at pressure up to 40 PSI
- Liquid for ease handling

PHYSICAL PROPERTIES

Appearance	Liquid
Colour	Amber
Odour	Neutral
Specific Gravity @ 20°C	1.190 - 1.200
pH (1%)	11.5 - 12.5

DIRECTIONS

Always add **MAGNUSPRAY 205** to water while mixing. Automatic feed and control services can be incorporated for safety, economy and quality controls.

Normal use concentrations are 0.5 to 5% concentrations.

Use at low concentrations without rinsing to provide in-process rust protection, depending on product used.

Use temperatures are from 16°C to 70°C depending upon product in use. Store liquids above 4°C.

Orapi Applied (S) Pte Ltd

No 26 Tuas Avenue 13 Singapore 638992

Tel: +65 6265 2888

Fax: +65 6268 6474

Website: www.orapiasia.com



TDS 5205 / 003 – 22/03/2022

1/2

The ORAPI Group designs, manufactures and markets "Highly Technical Solutions" for Maintenance Repair and overhaul of machines and equipments. The Group is present in over 100 countries with 32 subsidiaries and an international network of import-distributors. The Group operates 7 manufacturing plants and 5 laboratories of R&D. ORAPI is certified ISO 9001 and ISO 14001.

STORAGE & SAFETY

If swallowed, DO NOT induce vomiting. Give water or milk to drink if victim is conscious. Seek medical attention. When contact with the eyes, flush eyes with copious amount of water for at least 15 minutes. Seek medical attention. If contact with skin, flush affected areas with copious amount of water for at least 15 minutes. Remove contaminated clothing, wash before re-use.

For further information please refer to the Safety Data Sheet.

PACKAGING

Ref: O-5205-O2..... Pail 25 L
Ref: O-5205-U2 Drum 205 L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.