



NZA BRIGHT

GALVANISATION - ANTICORROSION SHINY

SALT SPRAY TEST > 400 HOURS

DESCRIPTION

Anti-rust coating that is very rich in zinc; used for cold galvanising to protect all metallic parts.

APPLICATIONS

- Rails, highway runners, welded joints on galvanised parts, agricultural frames and equipment.
- Chain link fences, barriers, piping, reservoirs and any metal structure requiring galvanising protection.
- All metal surfaces (iron, steel, galvanised metals and light alloys) particularly exposed to humid and marine environments.
- Not to be applied to surfaces subjected to temperatures >300°C.
- Galvanisation of new constructions or retouching after damage, shock or soldering

PRODUCT BENEFITS

- Packaging of 1 kg tins and 5 kg buckets **comply with DIRECTIVE 2004/42/EC** – category i: special function single-component coating, VOC rate < 500g/l (2010).
- Dries rapidly.
- Can be painted over.
- Leads to durable passivation of treated surfaces, which is strengthened over time through formation of a ferrous-zinc alloy.
- Formulated from zinc flakes.
- Shiny metallic aspect.
- Resists chemical products (except strong acids), the elements and corrosion extremely well.
- Complies with ISO 12944 standards.
- Provides safer handling than butane canisters.
- Gives better coverage than 'Galva butane,' with approx. 30% more active product.

PHYSICAL PROPERTIES

Aspect after drying Shiny
 Colour Metallic grey
 Density 1.4
 Drying time (dust-free) 15 minutes (dry-to-touch) - 12h (complete)

PHYSICAL PROPERTIES (NEXT)

Coverage	1.5 to 3 m ² /aerosol – 9 to 12 m ² /kg in bulk
Non-volatile matter	>60%
% metal	> 80% of dry film
Purity of zinc	>99.9%
Viscosity	190 cSt

DIRECTIONS FOR USE

Remove all pulverulent rust, scale, and grease from the surface of the metal.
Apply product to clean and dry surfaces using a brush, roller, or aerosol.

Aerosol: Shake well for 1 minute so that the pea can mix the product.
Spray the product evenly, approximately 20 cm from the surface. Do not allow product to run.
After use, quickly turn the aerosol upside down and press the actuator to empty the valve.
Propellant GAS: non-flammable = CO₂.

PACKAGING

650 ml aerosol	Ref. O 706 A4	x 12
1 kg box	Ref. O 706 B7	x 6
5 kg bucket	Ref. O 706 S1	x 2
200 kg drum	Ref. O 706 U2	x 1

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.