

TECHNICAL DATA SHEET

9200



ORASOLV 2000

Safety Solvent For Electrical Equipment

DESCRIPTION

ORASOLV 2000 (f.ka.TESTRASOL 2000 / PLC-400) is a powerful non-conductive and non flammable industrial solvent and degreasing agent developped for removing stubborn carbonized greases, sticky oil and synthetic fluids with a high evaporation rate leaving no residues behind.

ORASOLV 2000 is a unique product for maintaining and improving the efficiency of all electrical equipment.

APPLICATIONS

ORASOLV 2000 is an effective solution for cleaning power tools, electrical motors, additing machines, typewriters, air-conditioning and refrigeration equipment, printing equipment, elevator, marine and industrial motor, switch gear, panel and belt convertors.

PRODUCT BENEFITS

- Versatile.
- Powerful solvency action (residual fuels, oils, greases, tars, gums, varnishes).
- Leaves No Oily Residue with its 100% volatile composition.
- Increase productivity thanks to quick evaporation rate reducing the drying process.
- Allows painting, bonding and lubrication immediately after usage.
- Non-flammable.
- Non-conductive.
- Safe and Non corrosive.
- Saves labor costs and downtime because machinery does not have to be shut down during cleaning.
- Contains no 1,1,1 Tri-chloroethane or C F C'S that harm the ozone layer.
- Economical.

PHYSICAL PROPERTIES

Appearance	Liquid
Odour	
Colour	Colourless
Flash point	None
Evaporation speed (ether = 1)	1.2
Toxicity	Low TLV 100ppm

APPROVALS

Orapi Applied (S) Pte Ltd

No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888

Fax: +65 6268 6474 **Web Site: www.orapi.com**



TDS 9200 / 001 - 28/05/2014

1/2



TECHNICAL DATA SHEET

ORASOLV 2000 meets all requirements of the U.S. Department of Agriculture for use as solvent in non processing areas of official establishments operating under the Federal meat and poultry products inspection program. Original USDA letter of acceptance is on file in the Home Office.

DIRECTIONS

<u>NOTE:</u> **ORASOLV 2000** can be used while equipment is running, but adequate precautions and ample ventilation should be provided.

DO NOT APPLY TO EQUIPMENT WHERE SPARKING OR ARCING MAY OCCUR UNLESS EQUIPMENT IS SWITCHED OFF. ENSURE **ORASOLY 2000** IS COMPLETELY DRIED BEFORE RESTARTING.

<u>SPRAY OR BRUSH METHOD:</u> Apply sufficient amount of **ORASOLV 2000** to cover the surface and allow several seconds for the soil and grease to liquefy. Follow this by a second application of fresh **ORASOLV 2000** to remove all dissolved and suspended soils. Use enough product to flush the surface completely clean, then wipe or blow dry with air. **ORASOLV 2000** leaves no residue.

<u>FOR DIP CLEANING:</u> Place **ORASOLV 2000** in a metal tank with a **tight cover** to prevent evaporation losses. Soak parts or equipment to be cleaned in the dip tank for several minutes and agitate to loosen dissolved deposits. Remove parts and flush with a small quantity of fresh **ORASOLV 2000** to remove traces of dissolved grease from the dip tank.

EQUIPMENT

Petro Sprayer Air Spray Wand

STORAGE & SAFETY

Two years, stored in closed original packaging in a cool and dry environment.

Aerosol: Do not expose to temperature exceeding 50°C. Do not use on incandescent, warm body or near a source of heat.

Always use in well ventilated areas. Wear gloves and glasses.

For further information please refer to the Material Safety Data Sheet.

PACKAGING

Ref. O-9200-O2 Drum 25L Ref. O-9200-J1 Pail 4 x 5L

Ref. O-9200-A3 Aerosol 12 x 450GM

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.

Orapi Applied (S) Pte Ltd

No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888

Fax: +65 6268 6474 **Web Site:** <u>www.orapi.com</u>

