



POOLSHOCK

SWIMMING POOL CHLORINE GRANULES

DESCRIPTION

POOLSHOCK is a powerful calcium Hypochlorite agent designed for effective disinfection. **POOLSHOCK** has an excellent bleaching action and removes blood stains, protein soils, starch, fat and other contaminants.

APPLICATIONS

POOLSHOCK finds widespread application as sanitizer for swimming pools, spas, food processing, beverage, brewery, and various industrial sanitizing applications.

POOLSHOCK will control the growth of algae and bacteria in static water systems and may be used to condition the water in industrial processes

PRODUCT BENEFITS

- **4 in 1 action** : Bactericide, fungicide, disinfects & deodorizes
- Fast dissolving
- Kills water-borne bacteria & dissolves algae
- Great for use in swimming pools, spas, and hot tubs
- Stabilised – reduces loss of chlorine to sunlight; Ideal for outdoor pools
- Fine particle size — quickly raises free chlorine

PHYSICAL PROPERTIES

Appearance	Granular
Colour	White
Odour.....	Chlorine
pH	Alkaline when dissolved in water
Specific Gravity @ 20oC.....	2.35
Flammability.....	Non combustible
Available chlorine.....	65%

DIRECTIONS FOR USE

POOLSHOCK should be diluted with water before use to recommended concentration.

Dilutions:

STATIC WATER SYSTEMS	: 10 - 100 mg/l
POOLS AND SPAS	: Approx. 20 ppm
FOOD PROCESSING	: 200 – 300 ppm

STORAGE & SAFETY

If swallowed, wash mouth thoroughly with water immediately. Seek urgent medical attention. Avoid contact with the skin and the eyes; flush affected areas with copious amount of water for at least 15 minutes. Seek medical advice.

If contact with the skin, brush powdered material from skin contact. Thoroughly wash exposed area with running water.

Remove contaminated clothing and launder before reuse. Seek medical attention if effects persist.

If inhaled and irritation occurs, stop operation and remove to fresh air. Seek medical attention if irritation persists. If not breathing, give artificial respiration, probably mouth to mouth.

For further information please refer to the Material Safety Data Sheet.

PACKAGING

Ref: O-4973-O4Drum 45 KG

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.

Orapi Applied (S) Pte Ltd

No 26 Tuas Avenue 13 Singapore 638992

Tel: +65 6265 2888

Fax: +65 6268 6474

Inquiries: sin.sales@orapi.com.sg

Web Site: www.orapi.com



TDS 4973 / 002 – 18/04/2017

2/2

The ORAPI Group designs, manufactures and markets " Highly Technical Solutions" for Maintenance Repair and overhaul of machines and equipments. The Group is present in over 100 countries with 32 subsidiaries and an international network of import-distributors. The Group operates 7 manufacturing plants and 4 laboratories of R&D. ORAPI is certified ISO 9001 and ISO 14001.