

RAIDER

Workshop Floor Degreaser

5410



DESCRIPTION

RAIDER is general purpose water based liquid cleaner and degreaser containing water soluble solvents. Safely removes dirt, grease and grime from all washable surfaces. Excellent for cleaning in workshops and factory amenity areas.

RAIDER is a powerful alkaline cleaner containing a blend of alkalis and detergents.

RAIDER is designed for effective cleaning of underground equipment scrubber boxes.

No Power Fade Out:

RAIDER overcomes the basic problem of power fade-out, which is common to other alkaline and neutral cleaners. When other cleaners lose their cleaning capabilities as the solution gets dirty **RAIDER** keeps on working effectively with maximum cleaning power.

APPLICATION

RAIDER is use on all washable surfaces including floors walls, metal and timber fixtures, factory equipment, machinery, engines, vents, exhaust fans, upholstery and plastic surfaces. Can be used through pressure washers, steam cleaners, automatic scrubbing machines, spray and wipe or manual washing methods.

PRODUCT BENEFITS

- Concentrated liquid.
- Contains alkalis and detergents
- Economical to use.
- Powerful cleaner - removes small box residues

PHYSICAL PROPERTIES

Appearance.....	Viscous liquid
Colour	Dark Red
Odour	Pine
pH (10%).....	12.38 ± 0.5
Density	1.03 ± 0.01g/cm ³
Cloud Point	44°C
Viscosity.....	265 ± 10cP
Detergent Type	Biodegradable surfactant
Flammability.....	Non-flammable
Use Concentration	1 part to 50 parts water.



APPROVAL / CONFORMANCE



DIRECTIONS FOR USE

GENERAL CLEANING:

Mix **RAIDER** at the rate of 1:50 parts water, if mixing a large volume add the product to the full volume of water where possible.

FACTORY MACHINERY & EQUIPMENT

Dilute 1 part with 1-5 parts water depending on degree of soil. Use spray on/wipe off or wash on/rinse off method. Allow product to remain in contact with surface for 2-3 min. Assist with scrubbing brush if necessary.

PLASTIC & VINYL UPHOLSTERY

Dilute 1 part with 5-10 parts water. Spray or wipe on, and wipe off with clean cloth.

DEGREASING ENGINES

Dilute 1 part with 3-5 parts water. For heavily soiled surfaces allow solution to soak for 15-20 minutes before rinsing with strong stream of water. Assist cleaning with brushing if necessary.

FLOOR CLEANING

Vinyl Floor: Dilute 1 part with 10-20 parts water depending on soil to be removed. Scrub and rinse thoroughly.

Terrazzo, Ceramic & Quarry Tiles: Dilute 1 part with 10-40 parts hot water depending on soil to be removed. Scrub and rinse thoroughly with clean water.

Concrete: Dilute 1:10 part with water. Scrub thoroughly and rinse with clean water.

Auto Scrubbing Machines: Dilute 1 part with 40 parts water for general cleaning. For heavy cleaning, degreasing, dilute 1 part to 20 parts water.

Pressure Washers Steam Cleaners: Recommended end use dilution for heavy cleaning 1:30. Medium duty cleaning 1:50. Experiment with dilutions to gain optimum results.

STORAGE & SAFETY

HAZARDOUS. Irritating to eyes and skin. Wear safety glasses & suitable gloves when handling.

For further information please refer to the Material Safety Data Sheet

PACKAGING

Ref: A-5410-O2 Pail 25L

Ref: A-5410-U2 Drum 205L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.

