

TECHNICAL DATA SHEET





RUST OFF

Inhibited Rust Remover

DESCRIPTION

The rapid penetrating action of **RUST OFF** (*f.k.a. D-RUST*) makes faster removal of rust and oxidation possible while special inhibitors reduce the attack on clean steel by 98%. **RUST OFF** is the rapid remover for rust on iron and steel.

APPLICATIONS

All types of cast iron and steel equipment, machinery, structural materials, pipes and parts can be cleaned rapidly with **RUST OFF** to prepare them for a primer coat.

PRODUCT BENEFITS

- Fast penetrating action
- Dissolves rust and scale on steel very rapidly
- Contains powerful inhibitor system to protect metals
- Concentrated formula which can be highly diluted
- Can be used in deep tank
- Saves time and labour costs
- Economical

PHYSICAL PROPERTIES

Туре	. Fast acting inhibited rust remover
Colour	
Odour	. Mild Spice
Flammability	
Composition	. Combined mineral acids and biodegradable surfactants with
	acid inhibitor

Orapi Applied (S) Pte Ltd No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888 Fax: +65 6268 6474 **Web Site: www.orapi.com**



TDS 9949 / 002 – 23/12/2015

1/2

The ORAPI Group designs, manufactures and markets "Highly Technical Solutions" for Maintenance Repair and overhaul of machines and equipments. The Group is present in over 100 countries with 32 subsidiaries and an international network of import-distributors. The Group operates 7 manufacturing plants and 4 laboratories of R&D. ORAPI is certified ISO 9001 and ISO 14001.



TECHNICAL DATA SHEET

DIRECTIONS

- 1. Scrape or brush off loose and flaking rust.
- 2. Spray or brush on **RUST OFF** to thoroughly wet the surface. For heavy rust re-spray as required.
- 3. Rinse off the dissolved rust with water.
- 4. Blow dry immediately or apply a neutralizing rinse, e.g. 30% **QUIKSOL** to protect the clean metal from re-rusting.

Once dry, the surface may be primer coated immediately.

<u>EQUIPMENT</u>

Poly Sprayer Trig Mist Sprayer

STORAGE & SAFETY

Two years, stored in closed original packaging in a cool and dry environment.

HAZARDOUS

CORROSIVE : Avoid contact with eyes and skin. Wear safety glasses if splashing is likely to occur. Wear rubber gloves if prolonged skin contact is expected. HARMFUL IF SWALLOWED.

For further information please refer to the Material Safety Data Sheet.

PACKAGING

Ref. O-9949-O2 Ref. O-9949-J1 Pail 25L Jerrycan 4 x 5L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.

Orapi Applied (S) Pte Ltd No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888 Fax: +65 6268 6474 Web Site: www.orapi.com



TDS 9949 / 002 – 23/12/2015

The ORAPI Group designs, manufactures and markets "Highly Technical Solutions" for Maintenance Repair and overhaul of machines and equipments. The Group is present in over 100 countries with 32 subsidiaries and an international network of import-distributors. The Group operates 7 manufacturing plants and 4 laboratories of R&D. ORAPI is certified ISO 9001 and ISO 14001.

2/2