

**SCALEX**Alkaline Permanganate

5770



## **DESCRIPTION**

**SCALEX** is designed to be used as part of a multi-stage process for the removal of complex metallic scales from jet engine components.

## **APPLICATIONS**





## **PRODUCT BENEFITS**

- Readily soluble in water
- Safe on steel and other relevant metals.
- Rapid and efficient metallic scale removal.

## **PHYSICAL PROPERTIES**

Appearance	Free-flowing, small granules
Colour	
Odour	Odourless
pH 1% Solution	13.5 <u>+</u> 0.2

## **APPROVALS / CONFORMANCES**

- Qualified to P&W SPMC 202
- Conforms to ARP 1755B.
- Approved by Garret
- Conforms to GE Aircraft Engines

# **DIRECTION FOR USE**

**SCALEX** is used as one part of a multi-stage cleaning process following component treatment in either an alkaline rust remover or acidic scale conditioner.



## **DIRECTION FOR USE**

When preparing a new bath, 3/4 fill with cold water, then carefully add **SCALEX** whilst agitating the solution. Fill tank to working level with water, then heat tank to operating temperature. When making additions to operating tank carefully dissolve, with gentle stirring, the required quantity of **SCALEX** into a bucket of cold water. The bucket of **SCALEX** solution should then be carefully added to the operating bath. Never add water to the dry powder or **SCALEX** to hot water or directly to the operating tank.

Concentration: 150 - 200 g/L Temperature: 80° - 93°C. Immersion Time: 15 - 30 minutes.

Following immersion in **SCALEX** a thorough water rinse is recommended. Spray rinse components over the **SCALEX** bath. Immerse components in an overflowing water rinse tank. Pressure spray rinse components upon removal from water rinse tank.

Our ORAPI Representative will supply full chemical control procedures.

## MATERIALS OF CONSTRUCTION COMPATABILITY

Tank Construction. Stainless steel is recommended for both tank and heating coil construction.

#### **STORAGE & SAFETY**

For further information please refer to the Material Safety Data Sheet.

#### **PACKAGING**

Ref: A-5770-S5	Pail 20Kg
Ref: A-5770-U1	Drum 200Kg

#### **WARRANTY**

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.

