

# TECHNICAL DATA SHEET

9707



# SPILL GONE

## Safe Oil Spill Dispersant

### **DESCRIPTION**

**SPILL GONE** is a high powered oil dispersant and solubiliser, used in cleaning up heavy oil and oil waste products from dock areas, harbors, decks, slips, bilges and sumps.

### **APPLICATIONS**

SPILL GONE is used by Marinas, Dry Docks, Coastal Refineries, Off Shore Oil Rigs, Steam Ship Companies, etc.

### **PRODUCT BENEFITS**

- High Dispersion Capacity
- Does not contain any aromatic or chlorinated solvent
- Non-Corrosive to metals, including zinc, alloys and aluminium
- Safe on paint works
- Low in toxicity, therefore it will not harm normal skin or marine life. (LD50 value <100mg/litre)</li>
- Neutral pH
- Biodegradable
- Non-Flammable
- Safe to use
- PSA approved

### PHYSICAL PROPERTIES

| Appearance  | Liquid.                          |
|-------------|----------------------------------|
| Colour      |                                  |
| pH (1%)     |                                  |
| Flash Point |                                  |
| Toxicity    | Passed by PSA                    |
|             | Biodegradable surfactants and di |

Orapi Applied (S) Pte Ltd

No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888

Fax: +65 6268 6474
Web Site: www.orapi.com





### TECHNICAL DATA SHEET

### **DIRECTIONS**

For oil spillage on water (in harbors, around oil rigs, storage areas, etc) :

spray **SPILL GONE** heavily over oily areas to thoroughly cover and blend with oil. Allow natural action of waves to slowly disperse oil . For faster dispersing and clean up, wait 15 to 20 minutes for complete penetration. Spray treated areas with water from high pressure hose.

### For oil spillage on dock and deck areas :

spray SPILL GONE over oil and allow to penetrate. Flush off with hose.

For sumps and bilges:- to emulsify and disperse bilge water and facilitate cleaning, initially add 200ml of **SPILL GONE** per 4 litres of bilge capacity, then follow up with 100ml per 4 litres of bilge water before pumping.

### STORAGE & SAFETY

Two years, stored in closed original packaging at ambient temperature.

### **APPROVALS**

Approved by Port of Singapore Authority (PSA)

### **PACKAGING**

Ref. O-9707-U2 Ref. O-9707-O2 Drum 205L Pail 25L

### WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.



No 26 Tuas Avenue 13 Singapore 638992 Tel: +65 6265 2888 Fax: +65 6268 6474

Web Site: www.orapi.com

