



SSC

HEAVY DUTY STAINLESS STEEL RENOVATOR / BRIGHTENER

DESCRIPTION

SSC is a water based solution blend of mineral acids and tenside-active agents designed to clean, renovate, brighten and deoxidize special non oxidizing steel that despite their strong resistance to chemical attacks and pitting which removed their shiny finishing surfaces.

APPLICATIONS

SSC is specially designed for use in construction industry, boilerworks, shipwards, trucking companies, railways, appliance manufacturer, and by all maintenance companies (for outdoor stainless steel structures)

SSC removes all dirt and corrosion from stainless steel trucks bodies and railway carriages.

SSC is recommended for all stainless steel parts heavily stained and oxydized.

SSC effectively removes heavy deposits, black stains, blue stains and oxidation caused by welding : Tanks, vessels...

PRODUCT BENEFITS

- Fast-acting
- Passivating properties to treated surfaces which eliminate further corrosion.
- Can be used for etching surfaces prior to coating or painting
- 100% soluble and easy to apply
- Leaves no residue.
- Non-flammable

PHYSICAL PROPERTIES

Appearance	Liquid
Density @20°C	1.15
Odour	Pungent
Color	Translucent
pH (1% solution)	1.5
Flash Point	None

Orapi Applied (S) Pte Ltd

No 26 Tuas Avenue 13 Singapore 638992

Tel: +65 6265 2888

Fax: +65 6268 6474

Inquiries: sin.sales@orapi.com.sg

Web Site: www.orapiasia.com



DIRECTIONS FOR USE

General cleaning : dilution 30% to 50% in water.

Apply solution with POLY PUMP SPRAYER, or manually with a brush. Allow few minutes to act and then flush with sufficient quantity of water. For stubborn stains or corrosion marks use a bristle brush or soft cotton mop. Drying is not necessary. Be sure POLY PUMP SPRAYER is thoroughly washed out with water after each use.

Heavy Duty cleaning : for renovation of materials : use neat.

Apply solution with POLY PUMP SPRAYER, or manually or by dipping. Allow few minutes to act and then rinse with sufficient quantity of water. Drying is not necessary.

Note: Do not use on anodized aluminium, copper, brass or chrome surfaces. Due to the large variety of steel it is recommended to do a preliminary test.

STORAGE & SAFETY

Two years, stored in closed original packaging at ambient temperature.

Combustible liquid, Contains petroleum distillate.

Store and use away from heat, sparks and open flame, and in well-ventilated area.

Avoid prolonged breathing of vapours. Protect skin, eyes, and mucous membranes.

Wear protective gloves, goggles/face shield, and protective clothing when handling this product. Harmful if swallowed.

For further information, please consult the Materials Safety Data Sheet.

PACKAGING

Ref : O-9534-O2 Pail 25L

Ref : O-9534-U2 Pail 205L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MARKS NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.

Orapi Applied (S) Pte Ltd

No 26 Tuas Avenue 13 Singapore 638992

Tel: +65 6265 2888

Fax: +65 6268 6474

Inquiries: sin.sales@orapi.com.sg

Web Site: www.orapiasia.com



TDS 9534 / 002 – 01/03/2018

2/2

The ORAPI Group designs, manufactures and markets " Highly Technical Solutions" for Maintenance Repair and overhaul of machines and equipments. The Group is present in over 100 countries with 32 subsidiaries and an international network of import-distributors. The Group operates 7 manufacturing plants and 4 laboratories of R&D. ORAPI is certified ISO 9001 and ISO 14001.