



ULTRA CLEAN

CLEANING TISSUES MOIST TOWELETTES

HANDS and SURFACES

DEFINITION

Tissues specially soaked in a solvent engineered for the removal of all stains
Contains a new-generation advanced-technological solvent made from plant extracts.

ADVANTAGES

Excellent grease remover. Solvent in compliance with new community regulations (free of chloride or fluoride solvents) Enables dissolving of all types of fatty substances. Cleans hands without water directly at site of use. Hypo-allergenic.

USES

Its tremendous solvent power on numerous products, such as grease, oil, tar, asphalt, soot . . . makes of this product a very efficient weapon against dirt.
Suitable for degreasing of mechanical parts and polluted systems: housing, engine blocks, cisterns . . .
Removes traces of grass, felt-tip pen, ink, adhesive residue, hot-melt adhesives . . .
Ideal for heating engineers due to its outstanding efficiency on combustion residue.
Cleans cables, mechanical parts, machine frames, aluminium profiles . . .
End-of-project or end-of-process wipe-down in order to leave the work neat and clean.

DESCRIPTION

Appearance: pink tissues
Scent: mandarin orange
Flash point (VC) (ASTM D 56): 69°C
Dimensions: 31 x 19 cm
Dielectric strength: > 40 KV
KAURI BUTANOL Index: > 80

INSTRUCTIONS

Ready-to-use tissues. Close the container well after each use so the tissues do not dry out.

PACKAGING

Containers of 70 tissues Ref. 5575s9

Factory & corporate headquarters
Parc Industriel de la Plaine de l'Ain
5, allée des Cèdres - 01150 Saint-Vulbas - France
Tel. +33 (0)4 74 40 20 20 - Fax +33 (0)4 74 40 20 21
www.orapi-maintenance.com

1/1

FT 575 / Index 05 - 06/02/2012

Knowledge of every application for which its products are used and of the conditions under which they are used is not available to ORAPI®. ORAPI® cannot assume responsibility for the suitability of its products for any given use or any specific purpose. The information contained here cannot under any circumstances take the place of preliminary tests that are essential to be carried out in order to check the suitability of the product in each particular case.