

## UNICOOL

4279

### Closed Circuit Corrosion Inhibitor III

#### DESCRIPTION

**UNICOOL** is a clear, deep blue coloured liquid for prevention of corrosion and scale formation in high performance diesel and conventional engines.

#### PRODUCT BENEFITS

- Exceeds the corrosion resistance specification of Australian Standard 2108-1977, antifreeze compounds and corrosion inhibitors for Engine Cooling Systems, at recommended levels.
- Compatible with ethylene glycol based antifreeze additives.
- Will not harm radiator or heater hoses.
- Solutions are blue and self-indicating

#### PHYSICAL PROPERTIES

Appearance .....	Liquid
Colour .....	Clear Blue
Specific Gravity@ 20C .....	1.081 – 1.091
pH ( 1 % solution).....	8.1 – 8.5

#### DIRECTIONS FOR USE

1. Drain and thoroughly flush engine cooling system and heater circuit. (Consult engine manufacturers' service manual if in doubt as to correct procedure).
2. Half fill the cooling system with clean water and add 30ml of **UNICOOL** per liter of total cooling system volume. Fill the cooling system with clean water and check water level after running engine for 10-15 minutes. If necessary, top up using 3%v/v solution of **UNICOOL** never top up using plain water. (Any **UNICOOL** spilled on paintwork should be washed off with clean water.
3. The cooling system should be drained, flushed and retreated with **UNICOOL** every 12 months or 20,000km.

**UNICOOL** should be dosed at 3%v/v. No harm will result from overdosing. Under dosing will result in reduction of product performance.

## STORAGE & SAFETY

If swallowed, and if more than 15 minutes from hospital, induce vomiting, preferably using Ipecac syrup or similar emetic. Seek URGENT medical attention. If splashed in eyes, flush with copious water for 15 minutes and seek medical advice if effects persist. Wash from skin with soap and water. Seek medical attention if effects persist.

*For further information please refer to the Material Safety Data Sheet.*

## PACKAGING

Ref: A-4279-O2 ..... Drum 25L

## WARRANTY

*The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.*